

ECA control

Factsheet

	ECA Control Eco	ECA Control 1 Essential	ECA Control 2 Training	ECA Control 3 ProTrainer
				
Suitable for EVAstream type	EVAstream NEXT 175	EVAstream NEXT 225 - 275 - 350 EVAstream NEXT 450 - 550	EVAstream NEXT 225 - 275 - 350 EVAstream NEXT 450 - 550	EVAstream NEXT 225 - 275 - 350 EVAstream NEXT 450 - 550
Available EVA web app functions	Start / stop Speed / timer	Start / stop Speed / timer	Start / stop Speed / timer 3 swim workouts	Start / stop Speed / timer 20 swim workouts
Connection EVA LED underwater lighting	Not available	Optional (extension)	Optional (extension) Compatible with swim workouts	Optional (extension) Compatible with swim workouts
Connection EVA Remote control	Optional (extension)	Optional (extension)	Optional (extension)	Optional (extension)
ECA Unit				
Dimensions	158 x 119 x 75 mm (lxbxh)	158 x 119 x 75 mm (lxbxh)	158 x 119 x 75 mm (lxbxh)	158 x 119 x 75 mm (lxbxh)
IP rating	IP20	IP20	IP20	IP20
Working temperature	-20°C tot 32°C, dry/condensation-free	-20°C tot 32°C, dry/condensation-free	-20°C tot 32°C, dry/condensation-free	-20°C tot 32°C, dry/condensation-free
Warranty	2 years factory warranty	2 years factory warranty	2 years factory warranty	2 years factory warranty
Electrical specifications (input)				
Connection voltage (Vac)	230 Vac 5W	230 Vac 10W	230 Vac 10W	230 Vac 10W
Pulse input (piezo-ready)	Not available	3x Piezo ready	3x Piezo ready	3x Piezo ready
Electrical specifications (output)				
PPM output	PPM 1	PPM 2	PPM 2	PPM 2
Lighting control output	Not available	DMX	DMX - EVA	DMX - EVA
Fan output 5W (power box ventilation)	Not available	24 Vdc 5W	24 Vdc 5W	24 Vdc 5W