

EVA System remote

Factsheet



EVA System remote	
Compatible with	EVAstream and EVAsubaqua
Usage environment	Indoor and outdoor
Display	2.7-inch monochrome, 400 x 240 pixels
Operation	Capacitive touch (works with wet fingers)
Wireless connection	WiFi 2.4 GHz
Encryption / Safety	Complies with MC and safety standards (EN 55032, EN 61000, etc.)
Functions EVAstream	Start/stop, speed, timer and training programs
Functions EVAsubaqua	On/off, colour selection, synchronisation with the EVAstream
IP rating	Remote Control: IP67 Wall Station: IP53
Dimensions control panel	214 x 71 x 15 mm (L x W x H)
Dimensions charging station	90 x 92 x 19 mm (L x W x H)
Weight	EVA System remote: 575 g
Stainless steel 316	Stainless steel 316
Warranty	2 years

Battery

Battery type	3.7 V rechargeable battery
Capacity	400 – 500 mAh
Charging method	Inductive charging via wall-mounted charging coil
Power supply for charging station	100–240 Vac, 50/60 Hz
Operating temperature	5 °C – 35 °C
Input voltage (power supply)	100 – 240 Vac, 50/60 Hz
Mounting (charging station)	Wall-mounted (dry area, outside zone 2)
Communication with ECA	WiFi 2.4 GHz
Compatibility	Not compatible with EVA products up to 2025; expandable with 2026 ECA unit